

AUSTCHIP

“Outstanding Performance, Reliability
Safety and Service”

Tel: 03 9764 5700
Fax: 03 9764 5800
1/8 Viewtech Place
Rowville Vic 3178
A.B.N. 85 082 617 776

MODEL – AUSTCHIP 100 4” WOODCHIPPER

ENGINE:

Standard: 13hp petrol
Cooling: Air cooled
Air Cleaner: Dry element fitted with pre cleaner
Transmission: Centrifugal clutch
Engine Mounting: Heavy duty anti vibration mounts
Fuel Capacity: 6 litres

CAPACITY/INFEED:

Capacity: 100mm (4 inch)
Infeed Chute: 550mm x 340mm X 440mm
Infeed Opening: 210mm x 180mm
Infeed Height: 1500mm
Discharge Height: 2200mm
Discharge Chute: Full 360 degree rotation – easy swing/pin locking

CHIPPER DISC HOUSING:

Disc Size: 600mm x 25mm
Disc Weight: 86kg
Disc Speed: 1430rpm
Bearings: Twin spherical roller bearings
Shaft: 50mm High tensile steel
Knives: Two knives made of hardened chipper steel. 60mm x 220mm x 10mm double edged. Knives are located in fully machined pockets and are reversible and resharpenable.
Anvil: Made from hard wearing Duraflex with four usable sides. Easy external adjustment.
Chipper Housing: 5mm plate front and back, 4m plate top hood and belly.
Fan Paddles: Four fan paddles are bolted on to the disc.

TRAILER:

Chassis: 50mm x 50mm x 4mm RHS chassis/75mm x 75mm x 6mm draw bar
Dimensions: Length 2.9m, Height 2.2m, Width 1.8m
Weight: 460kg
Suspension: Leaf spring
Springs: 750kg capacity
Wheels/Tyres: Alloy wheels fitted with 6.00 x 9 x 6 ply tyres.
Jockey Wheel: Wind up type
Tow Coupling: As specified by client

All options and client special variations will conform to Government Safety Standards. Austchip reserves the right to change the specifications without notice.

AUSTCHIP – WORLD CLASS MACHINES MADE IN AUSTRALIA

Visit our website: www.austchip.com
Email inquiries: austchip@optusnet.com.au